

## SP Series wheeled Tractor



### PRODUCT FEATURES

- ◆ YTO engine is assembled to provide high horse power along with low fuel consumption and strong power.
- ◆ 16F+8R shuttle shift transmission can provide a reasonable velocity distribution, and a good operating adaptability.
- ◆ Options Germany LUK independently controlled dual clutch, high reliability and available operation during gear shifting.
- ◆ Adjustable wheel tread, Air brake and tire all come with options.

## TECHNICAL PARAMETERS

Product Model	1404	1504
Drive Type	4 × 4	
overall dimension ( mm )	Length	4800
	Width	2545
	Height ( with Cab )	3230 ( to top of air filter )
wheel base	2580	
Mi. Ground Clearance(mm)	470	470
Wheel Tread(mm)	Front	1750、1850 ( as factory set ) 、1950
	Rear	1750 ~ 2120 ( 1850 as factory set )
Structure Weight ( kg )	With Cab	5050
Counter weight ( kg )	Front	400
	Rear	540
Engine	Model	LR6M3Z-23
	Number of Cylinder	6
	Bore × stroke	110 × 125
	Rated power ( KW )	103      110.3
	Rated Speed	2300
Max traction force ( KN )		32
Max PTO power ( KW )		87.5      93.8
PTO Rotating Speed(r/min)		540/1000(option:540/760,760/850,760/1000)
Tyre	Front	14.9-26
	Rear	18.4-38
Gearbox	F16+8R	
Speed (Km/h)	1.37~30.5	

NOTE: The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

### K&F International Co.,Ltd

Addresss: Room 602, Building 3-2, Luoyang National University Science Park, China(Henan) PFTZ  
Postal Code: 471001.  
Tel: +86-379-6999 7655.  
Mob: +86-136 08666116.  
Fax: +86-379-6999 7655.  
Email: kf@kfinternational.com.cn  
Web Site:  
[Http://www.kfinternational.com.cn](http://www.kfinternational.com.cn)  
[Http://www.kf-international.com](http://www.kf-international.com)

